## **Annex 2 – Specified Equipment**

Item	Full Product Description	Product Code
1	32amp double pole 3-module isolator c/w 1 x 32amp double pole switch & 1 x BS88 fuse carrier & BS 88 LD fuse link, pre-wired for one upward circuit, earth block and ABS gland plate 2 x 20mm grommet. Test probe facility. Pre-wired with the following cable tails	TOFCO-Z-TYPE 1SK-PFI
	<ul> <li>2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> </ul>	
2	<ul> <li>1 x 6amp BS88 fuse</li> <li>32amp double pole 3-module isolator c/w 1 x 32amp double pole switch &amp; 2 x BS88 fuse carriers &amp; 2 x BS88 LD fuse links, pre-wired for upward circuits, earth block and ABS gland plate 2 x 20mm grommet. Test probe facility. Pre-wired with the following cable tails</li> </ul>	TOFCO-Z-TYPE 2SK-PFI
	<ul> <li>2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> <li>2 x 6amp BS88 fuses</li> </ul>	
3	32amp double pole 3-module isolator c/w 1 x 32amp double pole switch & 2 x BS88 fuse carriers & 2 x BS88 LD fuse links, pre-wired for one upward circuit and one spur circuit, earth & neutral blocks. Brass gland plate 1 x 20mm grommet & 1 x BW20 brass compression gland fitted. Test probe facility. Pre-wired with the following cable tails	TOFCO-Z-TYPE 3SK-PFI
	<ul> <li>2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> <li>2 x 6amp BS88 fuses</li> </ul>	
4	32amp double pole 4-module isolator c/w 1 x 32amp double pole switch & 3 x BS88 fuse carriers & 3 x BS88 fuses, pre-wired for three upward circuits, earth & neutral blocks. ABS gland plate 2 x 20mm grommets.  • 2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm	TOFCO-ZA-TYPE 4SK- PFI
	<ul> <li>2 No. onlin sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> <li>3 x 6amp BS88 fuses</li> </ul>	
5	32amp double pole 4-module isolator c/w 1 x 32amp double pole switch & 3x BS88 fuses, pre-wired for two upward circuits & one spur circuit, earth & neutral blocks. Brass gland plate 1 x 20mm grommet & 1 x BW brass compression gland.  • 2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm	TOFCO-ZA-TYPE 5SK- PFI
	<ul> <li>2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> <li>3 x 6amp BS88 fuses</li> </ul>	
6	32amp double pole 4-module isolator c/w 1 x 32amp double pole switch & 3 x BS88 fuses, pre-wired for one upward circuit & two spur circuits, earth & neutral blocks. Extension box with brass gland plate 1 x 20mm grommet & 2 x BW brass compression gland.	TOFCO-ZA-TYPE 6SK- PFI
	<ul> <li>2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> <li>3 x 6amp BS88 fuses</li> </ul>	
7	FESTIVE LIGHTING UNIT  32amp double pole isolator 2 x 4-module stackable isolators c/w 1 x 32amp double pole switch & 3 x BS88 fuses, pre-wired for two upward lantern circuits & 1 x festive circuit, protected via 1 x RCBO and controlled via 1 x 7 day digital programmable time clock. Neutral and earth connector blocks.	TOFCO-ZA-TYPE 7SK- PFI
	<ul> <li>Pre-wired with -</li> <li>2 No. 6mm sq double insulated colour coded Live and Neutral cable tails x 350mm long.</li> <li>1 No. 6mm sq tri-rated earth cable x 350mm.</li> <li>3 x 6amp BS88 fuses</li> </ul>	
8	DW Windsor – Kirium Pro Mini LED Luminaires – 3000K – ZHAGA Receptacle – Philips SR Driver – CLO.	
	The above luminaire recommended for mounting at 5-6 metres and available in 4,8,16 LEDs suitable for footpaths, cycle ways and residential roads.  Wattage and Photometric subject to lighting class and design	Reference: Subject to Lighting Class and Design
9	DW Windsor – Kirium Pro 1 LED Luminaires – 3000K – ZHAGA Receptacle – Philips SR Driver – CLO.	
	The above luminaire recommended for mounting at 5-8 metres and available in 8,16,24,32 LEDs suitable for footpaths, cycle ways, pedestrian crossings (@4000k) and residential roads.	Potoropos Cubicat to
	Wattage and Photometric subject to lighting class and design	Reference: Subject to Lighting Class and Design

Item	Full Product Description	Product Code
10	DW Windsor – Kirium Pro 2 LED Luminaires – 3000K – ZHAGA Receptacle – Philips SR Driver – CLO.  The above luminaire recommended for mounting at 6-10 metres and available in 32, 48, 64 LEDs suitable for main roads, car parks and conflict area lighting.  Wattage and Photometric subject to lighting class and design	Reference: Subject to Lighting Class and Design
11	DW Windsor – Kirium Pro 3 LED Luminaires – 3000K – ZHAGA Receptacle – Philips SR Driver – CLO.	Lighting Glass and Boolgin
	The above luminaire recommended for mounting at 8-15 metres and available in 64, 80, 98, 128 LEDs suitable for main roads and motorways.  Wattage and Photometric subject to lighting class and design	Reference: Subject to Lighting Class and Design
12	MALLATITE COLUMNS [BLACK OR GREEN] 5M POST TOP	01 05 6895
13	MALLATITE COLUMNS [BLACK OR GREEN] 5M SIDE ENTRY C/W 1.0M SINGLE ARM BRACKET	01 05 6896 + 02 1000 0748/0752
14	MALLATITE COLUMNS [BLACK OR GREEN] 6M POST TOP	01 06 5401
15	MALLATITE COLUMNS [BLACK OR GREEN] 6M SIDE ENTRY C/W 1.0M SINGLE ARM BRACKET	01 06 5401 + 02 1000 0748/0752
16	MALLATITE COLUMNS [BLACK OR GREEN] 8M POST TOP	01 08 5514
17	MALLATITE COLUMNS [BLACK OR GREEN] 8M SIDE ENTRY C/W 1.5M SINGLE ARM BRACKET	01 08 0224 + 02 1500 0741/0745
18	MALLATITE COLUMNS [BLACK OR GREEN]  10M POST TOP	01 10 5649
19	MALLATITE COLUMNS [BLACK OR GREEN]  10M SIDE ENTRY C/W 1.5M SINGLE ARM BRACKET	01 10 0542 + 02 1500 0741/0745
20	MALLATITE COLUMNS [BLACK OR GREEN] 12M POST TOP	01 12 5650
21	MALLATITE COLUMNS [BLACK OR GREEN]  12M SIDE ENTRY C/W 2M SINGLE ARM BRACKET	01 12 2076 + 02 2000 0819/1778
22	MALLATITE COLUMNS [BLACK OR GREEN]  12M SIDE ENTRY C/W 2M TWIN ARM BRACKET	01 12 2076 + 02 2000 0889/1848
23	MALLATITE COLUMNS [BLACK OR GREEN] 8M HEAVY DUTY XMAS POST TOP	01 08 6294 + B1677
24	MALLATITE COLUMNS [BLACK OR GREEN] 8M HEAVY DUTY XMAS C/W 1.5M BRACKET	01 08 6294 + B0819/0819
25	MALLATITE COLUMNS [BLACK OR GREEN]  10M HEAVY DUTY XMAS POST TOP	01 10 6295 + B5033
26	MALLATITE COLUMNS [BLACK OR GREEN]  10M HEAVY DUTY XMAS C/W 2.0M BRACKET	01 10 6295 + B1417/1779
27	Urban Control - ZHAGA DALI NODE (GPS TYPE)	UN320-SP-PS3-D3-MA5- H3-RC3-GT1
28	Numbering System Charled Endirect -01935 817444	



